




GENERAL SAFETY PRODUCTS

Code	Description	
	<p>SAFETY SHOWERS AND EYEWASH STATIONS</p> <p>The Spraydrench range is made from stainless steel in SA to highest quality standards. They must be plumbed in to normal half inch water supply which should be regulated to max 3 bar pressure, on which flow rates below are rated. A 40 mesh strainer between water supply inlet and eye wash or shower valve is strongly recommended.</p>	
56111	<p>Eyewash - Wall Mounted</p> <p>Manual operation, flow rate 15 litres/min through 2 aerator nozzles. Space required 300x300mm, 400mm high, mass 5kg</p>	<p>56111 Eyewash</p>
56121	<p>Eyewash Plus</p> <p>Platform operated, footprint 400x600mm, 980mm high, mass 10kg. Other specs as above</p>	<p>56121 Eyewash Plus</p>
56211	<p>Single Combination</p> <p>Combination eyewash and body shower. Manually operated eyewash station with specs as above. Manually operated shower with single nozzle, flow rate 72 litres/min, footprint 900x900mm, 2200mm high, mass 20kg</p>	<p>56211 Single Combination</p>
56221	<p>Single Combination Plus</p> <p>As above, platform operated shower, twin nozzles with flow rate 100litres/min, footprint 900x1350mm, mass 45kg</p>	<p>56221 Single Combination Plus</p>
56311	<p>Double Combination</p> <p>Combination manually operated eyewash, specs as above. Manually operated full body shower with 15 nozzles delivering 147 litres/min. Footprint 900x800mm, 2350mm high, mass 38kg</p>	<p>56311 Double Combination</p>
56321	<p>Double Combination Plus</p> <p>As above, platform operated shower, footprint 900x1350mm, mass 55kg</p>	<p>56321 Double Combination Plus</p>
Code	Description	Packing & Price Breaks
	<p>SAFETY SIGNS</p> <p>Standardised pictograms in ABS plastic</p>	
5243	290 Square	1 or 50
5241	150 Square - made to order	10
5242	190 Square - made to order	10
5244	440 Square - made to order	10
5245	Caution Wet Floor	1 or 10
	<p>Special Signs - made to order</p> <p>5245</p>	
	<p>SAFETY WALK</p> <p>3M's anti-slip floor strips for applications on wet or slippery tiles and public walkways. All self adhesive 18,3 metre rolls</p>	
5281	50mm Grey Resillient	1 or 4
	Anti-Slip in showers or barefoot areas	
5285	50mm Black Conformable	1 or 4
	Aluminium backed for high traffic or uneven surfaces	
5289	50mm General Purpose	1 or 4
5291	100mm General Purpose	1 or 4
	Plain back anti-slip material for smooth surfaces	
	<p>WELDING SCREEN CURTAINS AND WELDING BLANKETS</p>	
5270	Gold PVC 1,3 m x required length	1
	300 micron, eyelets every 30cm, 3cm hem, made to order	
5271	Strip Curtain Screen 2m x 2m	1
	Complete in movable frame, strips 200mm x 2m	
5272	Ceramic Welding Blanket	1
	Standard width 1m x required length. Made to order	



5285 Safety Walk



5270 Welding Screen