



# FALL PROTECTION



| Code  | Description  | Comments  | Avail. |   |
|-------|--|---|--------|---|
| 52631 | <b>Harness and Double Lanyard - permanently attached</b><br>IronMan Full Harness - double web lanyard S  | As 52630 above, with forked lanyard & 2 snap hook connectors  | S      |  <p>52631</p>  |
| 52640 | IronMan Full Harness - double web lanyard W  | As 52630 above, forked lanyard & 2 wide opening scaffold-hook connectors  | S      |   |
| 52635 | <b>Harness Only - requires separate lanyard</b><br>Nylon webbing 75mm and 45mm, adjustable for size. SANS 50361. See lanyard options below<br>IronMan Full Harness   | Five-point anchorage: 2 on hips, and 2 on shoulders & 1 at back for rescue.   | M      |  <p>52635</p>  |
| 52637 | IronMan Full Harness   | One-point rear anchorage & waistbelt  | S      |   |
| 52614 | <b>Lanyard and Connecting Device</b><br>Lanyard incorporates a shock-absorbing element to cushion a fall, and connectors. All to SANS 50354 & 50355<br>Web Lanyard - 2m S  | 45mm Webbing and 2 snap hooks   | S      |  <p>52614</p>  <p>52617</p>  <p>52645</p>  <p>52647</p>  <p>52639</p>  <p>52641</p>  <p>52642</p> |
| 52615 | Web Lanyard - 1m S   | 45mm Webbing and 2 snap hooks   | M      |   |
| 52616 | Web Lanyard - 2m C   | 45mm Webbing and 2 carabiners   | M      |   |
| 52617 | Rope Lanyard - 2m C  | 12mm Nylon rope and 2 carabiners  | M      |   |
| 52618 | Chain Lanyard - 2m T   | Chain, 1 snap hook and 1 toggle   | M      |   |
| 52619 | Double Web Lanyard - 2m S  | 45mm Webbing and 3 snap hooks   | M      |   |
| 52645 | Rescue Web Lanyard - 2m WS   | 45mm Webbing and 1 snap hook, 1 scaffold-hook and stirrup safety step   | S      |   |
| 52646 | Elasticated Lanyard - 2m W   | Elasticated lanyard, 1 snap hook & 1 wide opening scaffold-hook. Reduces lanyard hassle   | M      |   |
| 52647 | Double Elasticated Lanyard - 2m W  | Elasticated lanyard, 1 snap hook & 2 wide opening scaffold-hooks. Reduces lanyard hassle  | M      |   |
| 52639 | <b>Combination Fall Arrest and Work Position Belt</b><br>Worn by power and telecom line workers. SANS 50358<br>IronMan Linesman Kit  | Complete Eskom-style linesman kit in carry bag. Combination full harness and work position belt, five-point anchorage, 1 double leg shockabsorber lanyard with scaffold-hooks, 1 work position lanyard with wear sleeve and carabiners and 2 endless anchorage slings 1.5m doubled over | S      |   |
| 52641 | <b>Work Position Belt</b><br>Worn by power and telecom line workers to position themselves around a pole while standing on a ladder or platform. The lanyard is permanently attached one side and has no shock absorbing element. SANS 50358. It is not a fall arrest system<br>IronMan Single Prong Belt - web lanyard WS | Wear-sleeve 2m lanyard, kidney support & 1 snap hook. Six tool loops  | M      |   |
| 52642 | IronMan Double Prong Belt - web lanyard WS   | Wear-sleeve 2m lanyard, kidney support, 1 screwgate carabiner hook & 6 tool loops   | M      |   |
| 52624 | IronMan Anchorage Sling - 1.0m   | Doubled over gives 0.5m   | M      |   |
| 52626 | IronMan Anchorage Sling - 3.0m   | Doubled over gives 1.5m   | M      |   |
| 52627 | IronMan Anchorage Sling - 4.0m   | Doubled over gives 2.0m, for large girders  | M      |   |

**Note:** There are many configurations of a fall-arrest system, and if further information or training in use of any product is required, please contact us.

**Availability Key:** S: Normally stocked M: Made to order, 2-week lead time